

STERLING

WATER SYSTEMS



**Cartridge
Filter
Housings**



**Drinking
Water
Systems**



Sterling

3/4" Filter Housings



H34

Wrench	O-Ring	Bracket
WR200	ORVH	BRK-1020

- 3/4" inlet/outlet housing with wrench and pressure relief
- Clear sump
- Whole house applications
- Accepts a wide range of 2-1/2" x 10" cartridges
- Maximum pressure: 125 psi
- Maximum temperature: 100°F



VH34

Wrench	O-Ring	Bracket
WR300	ORVH	BRK-VIH

- Valve-in-head 3/4" inlet/outlet housing with wrench & pressure relief
- Turning the valve closes both inlet & outlet and relieves the pressure simultaneously, making cartridge change-out simple & quick
- Accepts a wide range of 2-1/2" x 10" cartridges
- Maximum pressure: 125 psi
- Maximum temperature: 100°F



HL34

Wrench	O-Ring	Bracket
WR400	OR3420	BRK-1020

- 3/4" inlet/outlet housing with wrench and pressure relief
- White sump
- Accepts a wide range of 2-1/2" x 20" cartridges
- Maximum pressure: 125 psi
- Maximum temperature: 100°F



HOT34

- 3/4" Hot water housing with wrench
- Maximum pressure: 125 psi
- Maximum temperature: 160°F

Sterling 1" High Flow Filter Housings



HJ10-1

Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1" inlet/outlet housing with wrench and pressure relief
- White sump
- Suitable for high flow applications
- Accepts a wide range of 4-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



HJ20-1

Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1" inlet/outlet housing with wrench and pressure relief
- White sump
- Suitable for high flow applications
- Accepts a wide range of 4-1/2" x 20" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F

Sterling — Point of Use Housings



USH05

Wrench	O-Ring	Bracket
WR200	ORVH	BRK-1020

- 1/4" inlet/outlet housing with mounting bracket and wrench
- Ideal for single faucet installations
- Accepts 2-1/2" x 5" cartridges
- Maximum pressure: 125 psi
- Maximum temperature: 100°F



USH10

Wrench	O-Ring	Bracket
WR200	ORVH	BRK-1020

- 1/4" inlet/outlet housing with mounting bracket and wrench
- Ideal for single faucet installations
- Accepts 2-1/2" x 10" cartridges
- Maximum pressure: 125 psi
- Maximum temperature: 100°F

Sterling Drinking Water Systems



DWSB-TFC-50

5 Stage Reverse Osmosis System

- Stages: 5 Micron Sediment, GAC, Carbon Block, R.O. Membrane, and Carbon Polisher
- Complete system including: faucet, storage tank, and installation fittings
- 50 gpd membrane
- Maximum TDS: 800



DWSB-50-PUMP

5 Stage Reverse Osmosis System

- Quiet booster pump increases water pressure to improve water quality and quantity
- 5 Stage Design (as shown above)
- Complete System (as shown above)
- Great output



QCRO-50

- Sanitary Quick Change Cartridges. Eliminates the mess associated with standard filter housings.
- Stainless steel bracket is strong and won't corrode
- Color coded filters makes for easy replacement
- All fittings are quick connect

STERLING
WATER SYSTEMS

12630 US Highway 33 N.
Churubusco, IN 46723
www.sterlingwatertreatment.com