

STERLING

WATER TREATMENT

Cartridge Filter Housings



Drinking Water Systems

...THE NEXT GENERATION



STERLING
WATER TREATMENT

www.sterlingwatertreatment.com



3/4" Filter Housings

HC34

Wrench	O-Ring	Bracket
WR-HC	OR-HC	BRK-HC

- 3/4" inlet/outlet housing
- Includes: wrench & pressure relief
- Whole house applications
- Accepts 2-1/2" x 10" cartridges
- Max Flow: 8 gpm
- Maximum pressure: 60 psi
- Maximum temperature: 100°F

NOTE: Flow rate will vary greatly depending on cartridge filter installed



HW34

Wrench	O-Ring	Bracket
WR300	ORVH	BRK-1020

- 3/4" inlet/outlet housing
- Includes: wrench & pressure relief
- Whole house applications
- Accepts 2-1/2" x 10" cartridges
- Max Flow: 8 gpm
- Maximum pressure: 100 psi
- Maximum temperature: 100°F

NOTE: Flow rate will vary greatly depending on cartridge filter installed



VHC34

Wrench	O-Ring	Bracket
WR-VHC	OR-VHC	BRK-VHC

- Valve-in-head 3/4" inlet/outlet
- Includes: wrench
- Turning the valve closes both inlet & outlet and relieves the pressure simultaneously
- Accepts 2-1/2" x 10" cartridges
- Max Flow: 6 gpm
- Maximum pressure: 100 psi
- Maximum temperature: 100°F

NOTE: Flow rate will vary greatly depending on cartridge filter installed



HL34-CLEAR

Wrench	O-Ring	Bracket
WR400	OR3420-CLEAR	BRK-1020

- 3/4" inlet/outlet housing
- Includes: wrench & pressure relief
- Clear sump
- Accepts 2-1/2" x 20" cartridges
- Max Flow: 15 gpm
- Maximum pressure: 80 psi
- Maximum temperature: 100°F

NOTE: Flow rate will vary greatly depending on cartridge filter installed



HL34

Wrench	O-Ring	Bracket
WR400	OR3420	BRK-1020

- 3/4" inlet/outlet housing
- Includes: wrench & pressure relief
- White sump
- Accepts 2-1/2" x 20" cartridges
- Max Flow: 15 gpm
- Maximum pressure: 100 psi
- Maximum temperature: 100°F

NOTE: Flow rate will vary greatly depending on cartridge filter installed



HOT34

Wrench	O-Ring	Bracket
WR300	OR3420	BRK-1020

- 3/4" inlet/outlet hot water housing
- Includes: wrench & pressure relief
- Max Flow: 8 gpm
- Maximum pressure: 100 psi
- Maximum temperature: 175°F

NOTE: Flow rate will vary greatly depending on cartridge filter installed



1/4" Filter Housings

USH05



Wrench	O-Ring
WR200	ORUSH

- 1/4" inlet/outlet housing
 - Includes: 3/8" adapters, bracket & wrench
 - Ideal for single faucet installations
 - Accepts 2-1/2" x 5" cartridges
 - Max Flow: 3 gpm
 - Maximum pressure: 100 psi
 - Maximum temperature: 100°F
- NOTE: Flow rate will vary greatly depending on cartridge filter installed

USH10



Wrench	O-Ring
WR200	ORUSH

- 1/4" inlet/outlet housing
 - Includes: 3/8" adapters, bracket & wrench
 - Ideal for single faucet installations
 - Accepts 2-1/2" x 10" cartridges
 - Max Flow: 3 gpm
 - Maximum pressure: 100 psi
 - Maximum temperature: 100°F
- NOTE: Flow rate will vary greatly depending on cartridge filter installed

1" High Flow Filter Housings

HJ10-1



Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1" inlet/outlet housing
 - Includes: wrench & pressure relief
 - White sump
 - Suitable for high flow applications
 - Accepts 4-1/2" x 10" cartridges
 - Max Flow: 25 gpm
 - Maximum pressure: 100 psi
 - Maximum temperature: 100°F
- NOTE: Flow rate will vary greatly depending on cartridge filter installed

HJ10-CLEAR



Wrench	O-Ring	Bracket
WR500	ORBB-CLEAR	BRK-J

- 1" inlet/outlet housing
 - Includes: wrench & pressure relief
 - Clear sump
 - Suitable for high flow applications
 - Accepts 4-1/2" x 10" cartridges
 - Max Flow: 25 gpm
 - Maximum pressure: 80 psi
 - Maximum temperature: 100°F
- NOTE: Flow rate will vary greatly depending on cartridge filter installed

HJ20-1



Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1" inlet/outlet housing
 - Includes: wrench & pressure relief
 - White sump
 - Suitable for high flow applications
 - Accepts 4-1/2" x 20" cartridges
 - Max Flow: 35 gpm
 - Maximum pressure: 100 psi
 - Maximum temperature: 100°F
- NOTE: Flow rate will vary greatly depending on cartridge filter installed

HJ20-CLEAR



Wrench	O-Ring	Bracket
WR500	ORBB-CLEAR	BRK-J

- 1" inlet/outlet housing
 - Includes: wrench & pressure relief
 - Clear sump
 - Suitable for high flow applications
 - Accepts 4-1/2" x 20" cartridges
 - Max Flow: 35 gpm
 - Maximum pressure: 80 psi
 - Maximum temperature: 100°F
- NOTE: Flow rate will vary greatly depending on cartridge filter installed

1.5" High Flow Filter Housings

HJ10-15



Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1.5" inlet/outlet housing
 - Includes: wrench & pressure relief
 - White sump
 - Suitable for high flow applications
 - Accepts 4-1/2" x 10" cartridges
 - Max Flow: 25 gpm
 - Maximum pressure: 100 psi
 - Maximum temperature: 100°F
- NOTE: Flow rate will vary greatly depending on cartridge filter installed

HJ20-15



Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1.5" inlet/outlet housing
 - Includes: wrench & pressure relief
 - White sump
 - Suitable for high flow applications
 - Accepts 4-1/2" x 20" cartridges
 - Max Flow: 35 gpm
 - Maximum pressure: 100 psi
 - Maximum temperature: 100°F
- NOTE: Flow rate will vary greatly depending on cartridge filter installed

Drinking Water Systems

Reverse Osmosis Systems



DWSB-TFC-50

5 Stage Reverse Osmosis System

5 Micron Sediment, GAC, Carbon Block, 50 gpd Membrane, and GAC post filter.



QCRO-50

5 Stage Reverse Osmosis System

Sanitary Quick Change Cartridges. Fast & Simple cartridge replacement.



CRS-3

Cyst, Virus & Chemical Reduction System



RO-LSV

Leak Detector Stop Valve

Specialty Systems



HMX-1

Heavy Metals Reduction System

With metered auto shut-off



NRS-1

Nitrate Reduction System

With metered auto shut-off

Pump Model R.O. Systems



DWSB-50-PermPump

4 Stage Reverse Osmosis System

Permeate Pump for higher line pressure and increased volume output.



QCRO-50-PUMP

5 Stage Reverse Osmosis System

Quiet booster pump increases water pressure to improve water quality and quantity.



Q1-CB1

Sanitary Quick Change Carbon Block



Q1-SR1

Sanitary Quick Change Scale Inhibitor & Carbon



S500SS

Scale Inhibitor System

