



STERLING

WATER TREATMENT

DF Series

Down Flow Non-Backwashing Filter



DF Series Filters are built with activated carbon filter media for the removal of taste, odor and chlorine.

- **Large Distributor Head** for easy bypass and plumbing installation.
- **Translucent Filter Tank** allows visual inspection of media level without disassembly.
- **One Inch Porting** allows higher flow rates with less pressure drop.
- **Union Connections** for quick servicing of unit.
- **Full Flow Bypass Valve** for easy to use, two handle valve allows you to water the yard or garden with raw water. Also, allows uninterrupted water service during periodic maintenance.

| Model Number | Media Volume (cu. ft.) | Flow Rate (gpm) | | Overall Dimensions | | | Pipe Size |
|--------------|------------------------|-----------------|------------|--------------------|-----|-----|------------------|
| | | Peak | Continuous | D | W | H | |
| DF10-1 | 1.0 | 10 | 3 | 14" | 10" | 52" | 3/4" or 1" |
| DF15-1 | 1.5 | 11 | 3 | 14" | 10" | 60" | |
| DF20-1 | 2.0 | 13 | 4 | 15" | 12" | 54" | |
| DF25-1 | 2.5 | 14 | 5 | 16" | 13" | 60" | |
| DF30-1 | 3.0 | 16 | 5 | 17" | 16" | 71" | |

NOTE 1: Above filters are not designed for continuous flow applications like ground water heat pumps.

