



- **Versatile**
- **Dome hole option available**
- **Semi-transparent media tank**

NBW Series

Automatic Backwash Filters

Suitable for use with the following media:

- **Activated Carbon** For chlorine, taste and odor reduction.
- **Catalytic Carbon** For the removal of chloramines, hydrogen sulfide and VOC's.
- **Filter Ag** Low Density Sediment removal down to 40 micron
- **Filter Sand** Sediment reduction down to 20 micron
- **Birm** Iron removal when raw water has sufficient dissolved oxygen
- **Calcium Carbonate** Raises the pH of acid water and removes turbidity. Use when pH is 6.0-6.8 and hardness is less than 5 gpg.
- **Neutralizer Blend** Raises the pH when incoming water pH is less than 6.0 or hardness is greater than 5 gpg.
- **Zeolite** Suspended solids and sediment reduction.

Features:

Rugged Motorized Piston Control. Reliable drive motor with power to stand up to iron, manganese, sediment, scale, and hardness over years of service.

Full Flow Bypass Valve. This is ideal for watering the yard or providing water while the unit is being serviced.

Non-corrosive Construction. Components are stainless steel, fiberglass, and polyethylene, eliminating rust and corrosion problems.



Model Number	Media Volume (cu. ft.)	Service Flow Rate (GPM)			Overall Dimensions			Pipe Size
		Backwash	Peak	Cont.	D	W	H	
NBW10	1.0	5	8	2	10"	10"	52"	3/4" or 1"
NBW15	1.5	5	9	3	10"	10"	62"	
NBW20	2.0	7	12	4	12"	12"	56"	

NOTE 1: Add suffix "-1S" if a 1" pipe size is desired. Example: NBW15-1S

NOTE 2: Add suffix "DH" if a dome hole is desired. Example: NBW15-DH

