



STERLING

WATER TREATMENT

NES Series Water Softeners

Easy to Use And Budget Friendly!



Easy To Program. Just push the button to set the time of day and hardness.

Safety Brine Valve. Eliminates messy overflow should a malfunction occur.

Optional Advanced Programming. Adjustment of each cycle duration; regeneration time; and days over-ride.

Salt Shelf. Allows the use of inexpensive salt and reduces the chance of salt bridging and mushing.

Rugged Resin Tank. Fiberglass construction, will never rust or corrode.

Vortex Distributor. Scrubs the resin each regeneration to extend the life of the softener.

Self Leveling Base. Compensates for unlevel floor.

Rugged Valve. Motorized piston for years of trouble free service.

Quick Release Drain Fitting. No threads to Leak. Merely pull clip to remove drain fitting.

Push-In Brine Line Fitting. Eliminates confusing ferrules and nuts that can cause leaks.

Stainless Steel Bypass. Operate with single handle. 3/4" or 1" female threads.



STERLING

WATER TREATMENT

www.sterlingwatertreatment.com



NES SERIES

SPECIFICATIONS

Model Number	Grain Capacity		Flow Rate (gpm)		Salt Storage (lbs.)	Dimensions *Inlet Height				Pipe Size
	Max.	Min.	Peak	Service		A	*B	C	D	
NES-0.75-S	22,500	18,000	14	6	200	52"	45.75"	23"	15"	3/4" or 1"
NES-1-S	30,000	24,000	14	8	200	56"	49.75"	27"	15"	
NES-1-5-S	45,000	36,000	13	10	200	62"	56"	28"	15"	
NES-2-S	60,000	48,000	14	12	200	56"	49.75"	30"	15"	
NES-2-5-S	75,000	60,000	15	14	200	62"	56"	32"	18"	

NOTE: If a 1" bypass is desired change suffix to 1S, example NES-1-1S.

SPACE-MAKER

Model Number	Grain Capacity		Flow Rate (gpm)		Salt Storage (lbs.)	Dimensions *Inlet Height				Pipe Size
	Max.	Min.	Peak	Service		A	*B	C	D	
NECS-0.75-S	22,500	18,000	14	6	150	43"	36.50"	23"	13"	3/4" or 1"
NECS-1-S	30,000	24,000	14	8	150	43"	36.50"	23"	13"	3/4" or 1"

NOTE: If a 1" bypass is desired change suffix to 1S, example NECS-1-1S.

NOTE: Service flow rate of control valve (only) is 20gpm @ 15 psig drop.

NECS



NES

