



- Reduces staining
- Sparkling dishes
- Bottom line savings
- Brighter laundry
- Protects plumbing

## PSX1 Series

**Hardness Reduction, Mechanical Filtration with Media Bed Disinfection**

- **Automatic Chlorine Generator.** Disinfects the unit and reduces iron and sulfur bacteria each regeneration.
- **Two Units in One.** Removes iron and hardness. Zeolite provides excellent filtration and chlorine resistant resin removes iron and hardness through ion exchange.
- **Adjustable Control.** Programming can be set to handle your water conditions.
- **Non-Corrosive Construction.** All components are made of fiberglass, stainless steel, or similar materials to provide many years of service.
- **Rugged Mechanical Piston Valve.** No solenoids or flapper valves to stick.
- **Full Flow Bypass Valve.** Easy to use, two handle valve allows you to water the garden or yard with raw water. Large porting prevents pressure drop.



**Chlorine Generator**

Picture may not be exact representation of product.

Model Number	Grain Capacity		Type of Regeneration	Flow Rate (gpm)		Overall Dimensions			Pipe Size
	Max.	Std.		Peak	Service	D	W	H	
PSX1-30	30,000	24,000	Meter/Time Clock	18	12	18"	28"	62"	3/4" & 1"
PSX1-45	45,000	36,000		23	14	18"	30"	56"	
PSX1-60	60,000	48,000		22	18	18"	31"	62"	
PSX1-75	75,000	60,000		23	19	18"	31"	74"	

NOTE: Service flow rate of control valve with bypass and meter is 27gpm @ 15 psig drop.

