



STERLING

WATER TREATMENT



PUN1-DH Series

Upflow Neutralizer

PUN1 Series Filters are designed to elevate the pH of acidic water. Raising the pH of acid water stops the corrosion of metal pipe fittings and fixtures. How high the pH is increased depends on the media chosen and contact time.

- **Large Fill Port** for easy replenishment of filter media.
- **Translucent Filter Tank** allows visual inspection of media level without disassembly.
- **One Inch Porting** allows higher flow rates with less pressure drop.
- **Upflow Design** prevents media from cementing.
- **Union Connections** for quick servicing of unit.
- **Full Flow Bypass Valve** for easy to use, two handle valve allows you to water the yard or garden with raw water. Also, allows uninterrupted water service during periodic maintenance.

Model Number	Media Volume (cu. ft.)	Flow Rate (gpm)		Overall Dimensions			Pipe Size
		Peak	Service	D	W	H	
PUN1-10-DH	1.0	8	6	14"	10"	52"	3/4" & 1"
PUN1-15-DH	1.5	12	8	14"	10"	62"	
PUN1-20-DH	2.0	14	10	15"	12"	56"	
PUN1-25-DH	2.5	18	12	16"	13"	62"	
PUN1-30-DH	3.0	20	14	17"	14"	74"	

NOTE 1: Filters are not designed for continuous flow applications like ground water heat pumps.

NOTE 2: How high the pH is raised depends on the hardness of the water; raw water pH; contact time, and media selected.

