





Anything But Ordinary! 5 Patents Pending

COMPLETE DISASSEMBLY NO TOOIS!





Advanced water USAGE HISTORY WITH PATTERN RECOGNITION BY DAY OF WEEK Anticipates Water Usage!







LASER SALT ALARM* WARNS YOU BEFORE YOU'RE OUT It Reminds!

PATENT PENDING CONACLE VALVE BODY Quick Repair

OTHER FABULOUS FEATURES



QUICK RELEASE HEAD REMOVAL FOR EASIER REPAIRS

VORTEX DISTRIBUTOR

LARGE DISTRIBUTOR TUBE FOR LESS PRESSURE LOSS AND HIGHER FLOW RATES

STERLING





HIGH FLOW BYPASS & "L" BRACKETS* "L" BRACKET* FOR CLOSE TO WALL INSTALL



ECO MODE USES LESS SALT THROUGH PROPORTIONAL BRINING



HIGH FLOW RATES FOR LESS PRESSURE LOSS



VACATION MODE TURNS OFF AUTOMATICALLY WHEN WATER IS USED

TOP SPIDER DISTRIBUTOR STAYS IN PLACE WHEN VALVE IS REMOVED



Freedom Valve

SPECIFICATIONS



Model Number	Grain Capacity		Type of	Service Flow Rate		Resin	Tank Size		Salt	Pipe Size
	Max.	Std.	Regeneration	Peak	Service	Volume	Softener	Brine Tank	Storage	•
XTS24	22,500	18,000	Meter	16	6	0.75	8 X 44	18 X 33	300 lbs.	3/4" & 1"
XTS30	30,000	24,000		18	8	1.00	9 x 48	18 X 33	300 lbs	
XTS45	45,000	36,000		18	12	1.50	10 x 54	18 X 33	300 lbs	
XTS60	60,000	48,000		21	16	2.00	12 x 48	18 X 33	300 lbs	
XTS75	75,000	60,000		21	18	2.50	13 x 54	18 X 33	300 lbs	
XTCS24	22,500	18,000	Meter-Space Saver	20	6	0.75	10 x 35	12x12x34	125 lbs	
XTCS30	30,000	24,000		21	8	1.00	10 x 35	12x12x34	125 lbs	

Space Saver

XTCS





