

- Reduces staining
- Sparkling dishes
- Bottom line savings
- Brighter laundry
- Protects plumbing

Hardness Reduction and Disinfector

Disinfector Series

- Automatic Chlorine Generator. Disinfects the unit and reduces iron and sulfur bacteria each regeneration.
- **Two Units in One.** Removes iron and hardness. Zeolite provides excellent filtration and chlorine resistant resin removes iron and hardness through ion exchange.
- Adjustable Control. Programming can be set to handle your water conditions.
- Non-Corrosive Construction. All components are made of fiberglass, stainless steel, or similar materials to provide many years of service.
- Rugged Mechanical Piston Valve. No solenoids or flapper valves to stick.
- Full Flow Bypass Valve. Simple to use valve allows you to bypass the unit for lawn sprinkling or during filter maintenance.

Brine

Model Number	Grain Capacity		Type of	Service Flow Rate		Overall Dimensions		
	Max.	Std.	Regeneration	Peak	Cont.	D	w	Н
ZX30	15,000	12,000	Meter/Time Clock	18	21	18"	28"	62"
ZX45	22,500	18,000		21	16	18"	30"	56"
ZX60	30,000	24,000		21	18	18"	31"	62"

NOTE: Service flow rate of control valve with bypass and meter is 27gpm @ 15 psig drop.





Brine and Chlorine